



brand of
VNT electronics s.r.o.
 Smetanovo nám. 104
 570 01 Litomyšl
 Czech Republic



Electronic training collar



d-control EASY

Transmitter

- Weight: 95 grams (transmitter, battery)
- Range: effective within approximately 200 meters
- Power supply: lithium button battery 3V CR2450

Collar

- Measurements: 34 × 40 × 62 mm
- Weight: 75 grams (a box, battery)
- Power supply: 3V lithium battery CR2
- Battery lifetime: 6 months on stand-by position
- Adjustable lengths of collar: 20–70 centimeters
- Waterproof, reliable in all conditions

Supply includes

- Collar, Neon trial valve
- Electrodes 13 mm and 17 mm
- Lithium battery CR2 3V, CR2450 3V
- Transmitter

Features

- Acoustic warning signal
- Four level of correcting electrical impulses
- Transmit frequency: 869 Mhz



d-control 250

Transmitter

- Weight: 95 grams (transmitter, battery)
- Range: effective within approximately 200 meters
- Power supply: lithium button battery 3V CR2450

Collar

- Measurements: 34 × 40 × 62 mm
- Weight: 75 grams (a box, battery)
- Power supply: 3V lithium battery CR2
- Battery lifetime: 6 months on stand-by position
- Adjustable lengths of collar: 20–70 centimeters
- Waterproof, reliable in all conditions

Supply includes

- Collar, Neon trial valve
- Electrodes 13 mm and 17 mm
- Lithium battery CR2 3V, CR2450 3V
- Transmitter

Features

- Acoustic warning signal
- Short alerting electrical impulse
- Range of correcting electrical impulses
- Eight level of correcting electrical impulses
- Transmit frequency: 869 Mhz



d-control 300

Transmitter

- Weight: 95 grams (transmitter, battery)
- Range: effective within approximately 200 meters
- Power supply: lithium button battery 3V CR2450

Collar

- Measurements: 34 × 40 × 62 mm
- Weight: 75 grams (a box, battery)
- Power supply: 3V lithium battery CR2
- Battery lifetime: 6 months on stand-by position
- Adjustable lengths of collar: 20–70 centimeters
- Waterproof, reliable in all conditions

Supply includes

- Collar, Neon trial valve
- Electrodes 13 mm and 17 mm
- Lithium battery CR2 3V, CR2450 3V
- Transmitter, Clip and keyholder

Features

- Acoustic warning signal
- Short alerting electrical impulse
- Range of correcting electrical impulses
- Nine level of correcting electrical impulses
- Transmit frequency: 869 Mhz

Electronic invisible fence



d-fence

Features

- First (warning) zone: continuously adjustable within 0,4–5 meters
- Second (correcting) zone: adjustable by steps within 0,4–1,6 meters
- Wire: single, isolated 0,75–1,5 mm²
- Lengths: maximum 450 meters
- Power supply: Adapter 230 V / 50 Hz, 15 V / 100 mA
- Boundary area: more than 1 hectare
- Intensity of electrical impulse can be adjusted on collar

Supply includes

- Collar
- Electrodes 13 mm and 17 mm
- Lithium battery CR2 3V
- Neon trial valve
- Transmitter
- Adapter
- 100 meters of single wire, profile 1 mm²
- Connectors of wires
- Aerial connector

Electronic no-bark collar



d-mute

Collar

- Measurements: 34 × 40 × 62 mm
- Weight: 65 grams (a box, battery)
- Power supply: 3V lithium battery CR2
- Battery lifetime: 6 months on stand-by position
- Adjustable lengths of collar: 20–70 centimeters
- Waterproof, reliable in all conditions
- Intensity of electrical impulse can be adjusted on collar

Supply includes

- Collar
- Electrodes 13 mm and 17 mm
- Lithium battery CR2 3V
- Neon trial valve

